#### Fuse Inserter/Extractor with Cover Function for 10.3x38 mm Fuses in Clips

0°C to 60°C, max. 70% r.h.

Type, Safety Note



ESO Fuse Inserter/Extractor (part of the delivery) Order required accessories separately

		See below: Approvals and Compl	iances
Description - Fuse inserter, extractor and cover in one component - Compact and cost-effective design - Terminal marking optional possible - Touch-safe according to IP20 - Captive fuse		Applications - Photovoltaic applications - Inverters - Battery charge controllers - String fuses - DC applications	
- Designed for use with CSC	) clips only	References Mating cover to ASO 10.	.3x38; CSO
			sheet, General Product Information, Distributor- s, Detailed request for product, Microsite,
Technical Data			
Fuse-Link	10.3 x 38 mm	Contact Resistance	< 5 m <b>Ω</b> at 100 mA
Mounting	Plug-in assembly		
Degree of Protection	IP20		
Admissible Ambient Temp.	-40 °C to 85 °C		
Climatic Category	40/085/21 acc. to IEC 60068-1		
Material	Thermoplastic black UL 94V-0		
Unit Weight	9.2 g		

#### **Approvals and Compliances**

Storage Conditions

Product Marking

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

#### Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: ESO

Approval Logo	Certificates	Certification Body	Description
c <b>FN</b> us	UL Approvals	UL	UR File Number: E39328
Product standards Product standards that are referenced			

Organization	Design	Standard	Description
(H)	Designed according to	UL 4248-1	Industrial Control Equipment
CSA Group	Designed according to	CSA C22.2 no. 4248.1	Industrial Control Equipment

# ESO 10.3x38

# Application standards

Application standards where the product can be used

IEC       Suitable for applications acc.       IEC/UL 62368-1       Audio/video, information and communication technology equipment - Part 1: Safety requirements	Organization	Design	Standard	Description
	IEC	Suitable for applications acc.	IEC/UL 62368-1	


## Compliances


The product complies with following Guide Lines

Identification	Details	Initiator	Description
CE	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
COMPLIANT	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
©	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

50.7 mm

# Dimension [mm]





1) Position for optional terminal marking (terminal block width: 5.2 mm, lettering field: 4.6x5.1 mm,

e.g. item 0818153 from Phoenix Contact)

## Variants

Туре	Packaging	Order Number
ESO 10.3x38	Bulk (50 pcs.)	0853.1250
ESO 10.3x38	Bulk (500 pcs.)	0853.1251

Availability for all products can be searched real-time: https://www.schurter.com/en/info-center/ support-tools/stock-check-distributors

## **Required Accessory**

## Description

CSO Heavy Duty Fuse Clip, 10.3 x 38 /10.3 x 85 mm, 1500 VAC/VDC, 32 A

10.3 x 38 / 10.3 x 85 mm	0751.0500
10.3 x 38 / 10.3 x 85 mm	0751.0501
10.3 x 38 / 10.3 x 85 mm	0751.0502
10.3 x 38 / 10.3 x 85 mm	0751.0503

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.