Clip, 10.3 x 38 mm, UR

20A (UL)	See below: Approvals and Compliances
<b>Description</b> - Through hole mounting	Applications - Combiner Boxes in Photovoltaic Systems References

Fuseholder to ASO 10.3x38

### Weblinks

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product, Microsite

### Technical Data

lecinical Data			
Fuse-Link	10.3 x 38 mm	Soldering Methods	Wave
Mounting	PCB		Soldering Profile
Terminal	Solder THT	Solderability	235 °C / 2 sec acc. to IEC 60068-2-20,
Rated current	20A (UL)		Test Ta, method 1
Degree of Protection	IP00	Resistance to Soldering Heat	260 °C / 10 sec acc. to IEC 60068-2-20,
Material: Terminals	see variants		Test Tb, method 1A
Unit Weight	4.1 g	Contact Resistance	< mΩ at 100 mA
Storage Conditions	0 °C to 60 °C, max. 70% r.h.		
Product Marking	I, Type, Certification marks		

#### **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

### Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 231660

Certificates	Certification Body	Description
UL Approvals	UL	UR File Number: E41738
e referenced		
Design	Standard	Description
Designed according to	UL 4248-1	Industrial Control Equipment
	JL Approvals e referenced Design	JL Approvals UL e referenced Design Standard

# 231660

# Application standards


Application standards where the product can be used

Organization	Design	Standard	Description
IEC	Suitable for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements
Compliances			
The product comp	olies with following Guide Lines		

	tar tollowing dalac Eirico		
Identification	Details	Initiator	Description
CE	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
<b>50</b>	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

**Dimension** [mm]

12 mm







Drilling diagram

## All Variants

Clip	Terminal	Material: Terminals	Order Number	
•	straight	Tin-Plated Bronze	7170.0470	

# Most Popular.

Availability for all products can be searched real-time: https://www.schurter. com/en/info-center/support-tools/stock-check-distributors

**Packaging Unit** 

Bulk (50 pcs.)