Socket, solder terminal, screened, 3.5 mm, 3-pole, straight, UK-Connector



Description

- Solder :
- Screw-on mounting , rear-side
- Data and Signal transfer
- Data and Signal Connectors 3-pole , shielded , straight
- Reinforced gold plating for increased insertions

See below: Approvals and Compliances

Characteristics

- Does not comply with the JAP or BPO standard

References

Alternative: Housing insulated 4802.2310

Weblinks

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product

10000 Insertions

Technical Data

Diameter	3.5 mm	Allowable Operation Tempe-	-20 °C to 70 °C
Number of Poles	3-pole	rature	
Ratings DC	1 A / 12 VDC	Terminal	solder terminal
Ratings AC	1 A / 12 VAC	Mounting	Screw-on mounting
Dielectric Strength	500 VDC		wall thickness max. 2.0mm
Insulation Resistance	> 10000 MΩ @ 500 VDC	Housing	screened
		Style	straight

Lifetime

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.


Compliances

The product complies with following Guide Lines


Identification	Details	Initiator	Description
Rohs	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

4802.2300

Dimensions [mm]



Diagrams



Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Data and Signal Plug/ Sockets	3.5	3-pole	solder terminal	4802.2300

Availability for all products can be searched real-time: https://www.schurter.com/en/info-center/support-tools/stock-checkdistributors

Packaging unit

100 Pcs

Mating Inlets/Plugs

Category / Description



Data and Signal Plug/Socket Overview complete

Plug, solder terminal, screened, 3.5 mm, 3-pole, straight, UK-Connector	4802.1300
Plug, solder terminal, insulated, 3.5 mm, 3-pole, straight, UK-Connector	4802.1310