



















Product Overview Power Entry Modules with Line Filter

www.schurter.com/en/pg06














Type	Mounting method Side	Plug Outlet	Protection class			
Rated Current AC max IEC UL: 2.5 A 6 A						
 <p>5008 IEC Appliance Inlet C8 with Filter, Front Side Mounting</p>	Snap-in/screw-on Front Side	C8 -	IP40			
Rated Current AC max IEC UL: 6 A 8 A						
 <p>CD-Bowdencable IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), Bowden Line Switch 1- or 2-pole, Voltage Selector (Step)</p>	Screw Front Side	C14 -	IP40			
Phase Out						
 <p>CG-Bowdencable With fuseholder 5x20 mm/6.3x32 mm, voltage sel. (series-parallel)</p>	Screw Front Side	C14 -	IP40			
Phase Out						
Rated Current AC max IEC UL: 8 A 8 A						
 <p>5707 IEC Appliance Inlet C14 or C18 with Filter, Protection Degree IP65 into the Appliance, Fuseholder 1- or 2-pole, Front or Rear Mounting</p>	Screw Front-/Rear-Side	C14 C18 -	IP65			
Rated Current AC max IEC UL: 10 A 8 A						
 <p>DD14 IEC Appliance Inlet C14 with Filter 2-Stages, Fuseholder 1- or 2-pole, Line Switch 2-pole</p>	Snap-in or screw-on Front Side	C14 -	IP40			
new						
 <p>DD12 IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole, Line Switch 2-pole</p>	Screw Front Side	C14 -	IP40			
new						
Rated Current AC max IEC UL: 10 A 10 A						
 <p>KFB1 IEC Appliance Inlet C14 with Filter, Line Switch 1-pole</p>	Screw Front Side	C14 -	IP40			
 <p>DA22 IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole, for PCB Mounting</p>	Screw Rear Side	C14 -	IP40			











Power Entry Modules with Line Filter (PG06)

	Type	Mounting method Side	Plug Outlet	Protection class	V-Lock	100
	KFB2 IEC Appliance Inlet C14 with Filter, Line Switch 2-pole	Screw Front Side	C14 -	IP40	•	
	DC12 IEC Appliance Inlet C14 with Filter, Line Switch 1- or 2-pole, Front or Rear Side Mounting	Snap-in/screw-on Front-/Rear-Side	C14 C18 -	IP40	•	•
	DC22 IEC Appliance Inlet C14 with Filter, Line Switch 1- or 2-pole, PCB Mounting	Screw Rear Side	C14 -	IP40	•	•
	DD22 IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole, Line Switch 2-pole, for PCB Mounting	Screw Rear Side	C14 -	IP40	•	•
	KMF IEC Appliance Inlet with Filter, Fuseholder 1- or 2-pole, Line Switch 2-pole	Snap-in Front Side	C14 C18 -	IP40	•	•
	CD IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), Line Switch 1- or 2-pole, Voltage Selector (Step)	Screw Front Side	C14 -	IP40	•	•
	CG IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), Line Switch 1- or 2-pole, Voltage Selector (Series-Parallel)	Screw Front Side	C14 -	IP40	•	•
	FKH IEC Appliance Inlet C14 with Filter, Fuseholder 1-pole, Line Switch 2-pole	Screw Front Side	C14 -	IP40	•	•
	FKI IEC Appliance Inlet C14 with Filter, Fuseholder 2-pole, Line Switch 2-pole	Screw Front Side	C14 -	IP40	•	•
	FKHD IEC Appliance Inlet C14 with Filter 2-Stage, Fuseholder 1-pole, Line Switch 2-pole	Screw Front Side	C14 -	IP40	•	•








Power Entry Modules with Line Filter (PG06)

	Type	Mounting method Side	Plug Outlet	Protection class	V-Lock 		
	FKID IEC Appliance Inlet C14 with Filter 2-Stage, Fuseholder 2-pole, Line Switch 2-pole	Screw Front Side	C14 -	IP40	•	•	
	Felcom_54 IEC Appliance Inlet C14 Modular Assembling Options	Snap-in Front Side	C14 F	IP40	•	•	
	KFA IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole, optional Voltage Selector (step switch)	Snap-in/screw-on Front-/Rear-Side	C14 -	IP40	•	•	•
	KFC IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), optional Voltage Selector (step switch)	Screw Front Side	C14 -	IP40	•	•	•
	CE IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5 x 20 mm or 6.3x32 mm, with or without voltage selector (series-parallel)	Screw Front Side	C14 -	IP40	•	•	•
	5200 IEC Appliance Inlet C14 with Filter, Fuseholder 1-pole	Snap-in/screw-on Front Side	C14 -	IP40	•	•	•
	5220 IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole	Snap-in/screw-on Front Side	C14 -	IP40	•	•	
	KFS IEC Appliance Inlet C14 with Filter	Screw Front Side	C14 -	IP40	•		
	KPF Filter for Backpack Mounting to KP01	Sandwich/rear-side Rear Side	- -	IP40		•	
 Phase Out	GRM2 IEC Appliance Inlet C14 with Line Switch, Fuseholder 1- or 2-pole, Voltage Selector (series-parallel), "Lock and Shield" Mounting,	Snap-in Rear Side	C14 -	IP40	•		

Power Entry Modules with Line Filter (PG06)

	Type	Mounting method Side	Plug Outlet	Protection class	V- Lock
 Phase Out	FGS IEC Appliance Inlet C14 with Filter, Front or Rear side Mounting	Snap-in/screw-on Front-/Rear-Side	C14 -	IP40	•
 Phase Out	KFX IEC Appliance Inlet C14 with Filter, Increased Dielectric Strength	Screw Front Side	C14 -	IP40	•
Rated Current AC max IEC UL: 10 A 15 A					
 new	DG12 IEC Appliance Inlet C14 with Filter, Circuit Breaker TA35 (recessed)	Screw Front Side	C14 C18 -	IP40 or IP65 / IP67	• •
	5123 IEC Appliance Inlet C14 or C18 with Filter, high attenuation, ECO design, Front- or Rear Side Mounting	Snap-in/screw-on Front-/Rear-Side	C14 C18 -	IP40	• •
	GRF2 IEC Appliance Inlet C14 with Shielding, "Lock and Shield" Mounting	Snap-in Rear Side	C14 -	IP40	•
	GRF4 IEC Appliance Inlet C14 with Filter, "Lock and Shield" Mounting	Snap-in Rear Side	C14 -	IP40	•
	5110 IEC Appliance Inlet C14 with Filter	Snap-in/screw-on Front Side	C14 -	IP40	•
	5120 IEC Appliance Inlet C14 or C18 with Filter, ECO design, Front- or Rear Side Mounting	Screw Front-/Rear-Side	C14 C18 -	IP40	• •
 Phase Out	5150 IEC Appliance Inlet C14 with High Frequency Filter, X2Y Technology, ECO design, Front- or Rear Side Mounting	Screw Front-/Rear-Side	C14 -	IP40	• •
	5145 IEC Appliance Inlet C14 or C18 with Filter, Circuit Breaker TA45	Screw Front Side	C14 C18 -	IP 40	•

Power Entry Modules with Line Filter (PG06)

Type	Mounting method Side	Plug Outlet	Protection class	V-Lock
 <p>DF12 IEC Appliance Inlet C14 with Filter, Circuit Breaker TA45 (recessed)</p>	Screw Front Side	C14 -	IP 40	• •
<p>Rated Current AC max IEC UL: 15 A 15 A</p>				
 <p>5003 Appliance Inlet DC Filter, ECO Design, Front- or Rear Side Mounting</p>	Snap-in/screw-on Front-/Rear-Side	Molex MLX -	-	
<p>Rated Current AC max IEC UL: 16 A 20 A</p>				
 <p>EC12 IEC Appliance Inlet C20 with Filter, Line Switch 2-pole</p>	Screw Front Side	C20 -	IP40	• •
 <p>5130 IEC Appliance Inlet C20 with Filter, ECO design, front or rear side Mounting</p>	Snap-in/screw-on Front-/Rear-Side	C20 -	IP40	• •
 <p>C20F IEC Appliance Inlet C20 with Filter, Front or Rear Side Mounting</p>	Snap-in/screw-on Front-/Rear-Side	C20 -	IP40	• •
 <p>C22F IEC Appliance Inlet C22 for hot Conditions, with Filter for high Temperatures, front side Mounting</p>	Snap-in/screw-on Front-/Rear-Side	C22 -	IP40	•
 <p>EF12 IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed)</p>	Screw Front Side	C20 -	IP 40	• •