




















Product Overview Power Entry Modules with Line Filter

www.schurter.com/en/pg06













Type	Mounting method Side	Plug Outlet	Protection class			
Rated Current AC max IEC UL: 2.5 A 6 A						
 <p>5008 IEC Appliance Inlet C8 with Filter, Front Side Mounting</p>	Snap-in/screw-on Front Side	C8 -	IP40			•
Rated Current AC max IEC UL: 6 A 8 A						
 <p>CD-Bowdencable IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), Bowden Line Switch 1- or 2-pole, Voltage Selector (Step)</p> <p>Phase Out</p>	Screw Front Side	C14 -	IP40		•	•
 <p>CG-Bowdencable With fuseholder 5x20 mm/6.3x32 mm, voltage sel. (series-parallel)</p> <p>Phase Out</p>	Screw Front Side	C14 -	IP40			•
Rated Current AC max IEC UL: 8 A 8 A						
 <p>5707 IEC Appliance Inlet C14 or C18 with Filter, Protection Degree IP65 into the Appliance, Fuseholder 1- or 2-pole, Front or Rear Mounting</p>	Screw Front-/Rear-Side	C14 C18 -	IP65		•	•
Rated Current AC max IEC UL: 10 A 8 A						
 <p>DD14 IEC Appliance Inlet C14 with Filter 2-Stages, Fuseholder 1- or 2-pole, Line Switch 2-pole</p> <p>new</p>	Snap-in or screw-on Front Side	C14 -	IP40		•	•
 <p>DD12 IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole, Line Switch 2-pole</p> <p>new</p>	Screw Front Side	C14 -	IP40		•	•
Rated Current AC max IEC UL: 10 A 10 A						
 <p>KFB1 IEC Appliance Inlet C14 with Filter, Line Switch 1-pole</p>	Screw Front Side	C14 -	IP40			
 <p>DA22 IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole, for PCB Mounting</p>	Screw Rear Side	C14 -	IP40		•	•












Power Entry Modules with Line Filter (PG06)

	Type	Mounting method Side	Plug Outlet	Protection class	V-Lock 
	KFB2 IEC Appliance Inlet C14 with Filter, Line Switch 2-pole	Screw Front Side	C14 -	IP40	•
	DC12 IEC Appliance Inlet C14 with Filter, Line Switch 1- or 2-pole, Front or Rear Side Mounting	Snap-in/screw-on Front-/Rear-Side	C14 C18 -	IP40	• •
	DC22 IEC Appliance Inlet C14 with Filter, Line Switch 1- or 2-pole, PCB Mounting	Screw Rear Side	C14 -	IP40	• •
	DD22 IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole, Line Switch 2-pole, for PCB Mounting	Screw Rear Side	C14 -	IP40	• • •
	KMF IEC Appliance Inlet with Filter, Fuseholder 1- or 2-pole, Line Switch 2-pole	Snap-in Front Side	C14 C18 -	IP40	• •
	CD IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), Line Switch 1- or 2-pole, Voltage Selector (Step)	Screw Front Side	C14 -	IP40	• • •
	CG IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), Line Switch 1- or 2-pole, Voltage Selector (Series-Parallel)	Screw Front Side	C14 -	IP40	• • •
	FKH IEC Appliance Inlet C14 with Filter, Fuseholder 1-pole, Line Switch 2-pole	Screw Front Side	C14 -	IP40	• •
	FKI IEC Appliance Inlet C14 with Filter, Fuseholder 2-pole, Line Switch 2-pole	Screw Front Side	C14 -	IP40	• •
	FKHD IEC Appliance Inlet C14 with Filter 2-Stage, Fuseholder 1-pole, Line Switch 2-pole	Screw Front Side	C14 -	IP40	• •








Power Entry Modules with Line Filter (PG06)

	Type	Mounting method Side	Plug Outlet	Protection class	V-Lock
	FKID IEC Appliance Inlet C14 with Filter 2-Stage, Fuseholder 2-pole, Line Switch 2-pole	Screw Front Side	C14 -	IP40	• •
	Felcom 54 IEC Appliance Inlet C14 Modular Assembling Options	Snap-in Front Side	C14 F	IP40	• •
	KFA IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole, optional Voltage Selector (step switch)	Snap-in/screw-on Front-/Rear-Side	C14 -	IP40	• • •
	KFC IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), optional Voltage Selector (step switch)	Screw Front Side	C14 -	IP40	• • •
	CE IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5 x 20 mm or 6.3x32 mm, with or without voltage selector (series-parallel)	Screw Front Side	C14 -	IP40	• • •
	5200 IEC Appliance Inlet C14 with Filter, Fuseholder 1-pole	Snap-in/screw-on Front Side	C14 -	IP40	• • •
	5220 IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole	Snap-in/screw-on Front Side	C14 -	IP40	• •
	KFS IEC Appliance Inlet C14 with Filter	Screw Front Side	C14 -	IP40	•
	KPF Filter for Backpack Mounting to KP01	Sandwich/rear-side Rear Side	-	IP40	•
 Phase Out	GRM2 IEC Appliance Inlet C14 with Line Switch, Fuseholder 1- or 2-pole, Voltage Selector (series-parallel), "Lock and Shield" Mounting,	Snap-in Rear Side	C14 -	IP40	•

Power Entry Modules with Line Filter (PG06)

	Type	Mounting method Side	Plug Outlet	Protection class	V-LOCK 		
	FGS IEC Appliance Inlet C14 with Filter, Front or Rear side Mounting	Snap-in/screw-on Front-/Rear-Side	C14 -	IP40	•		
Phase Out							
	KFX IEC Appliance Inlet C14 with Filter, Increased Dielectric Strength	Screw Front Side	C14 -	IP40	•		
Phase Out							
Rated Current AC max IEC UL: 10 A 15 A							
	DG12 IEC Appliance Inlet C14 with Filter, Circuit Breaker TA35 (recessed)	Screw Front Side	C14 C18 -	IP40 or IP65 / IP67	•	•	
new							
	5123 IEC Appliance Inlet C14 or C18 with Filter, high attenuation, ECO design, Front- or Rear Side Mounting	Snap-in/screw-on Front-/Rear-Side	C14 C18 -	IP40	•	•	
	GRF2 IEC Appliance Inlet C14 with Shielding, "Lock and Shield" Mounting	Snap-in Rear Side	C14 -	IP40			
	GRF4 IEC Appliance Inlet C14 with Filter, "Lock and Shield" Mounting	Snap-in Rear Side	C14 -	IP40		•	
	5110 IEC Appliance Inlet C14 with Filter	Snap-in/screw-on Front Side	C14 -	IP40		•	
	5120 IEC Appliance Inlet C14 or C18 with Filter, ECO design, Front- or Rear Side Mounting	Screw Front-/Rear-Side	C14 C18 -	IP40	•	•	
	5150 IEC Appliance Inlet C14 with High Frequency Filter, X2Y Technology, ECO design, Front- or Rear Side Mounting	Screw Front-/Rear-Side	C14 -	IP40	•	•	
Phase Out							
	5145 IEC Appliance Inlet C14 or C18 with Filter, Circuit Breaker TA45	Screw Front Side	C14 C18 -	IP 40		•	

Power Entry Modules with Line Filter (PG06)

Type	Mounting method Side	Plug Outlet	Protection class	V-Lock
 <p>DF12 IEC Appliance Inlet C14 with Filter, Circuit Breaker TA45 (recessed)</p>	Screw Front Side	C14 -	IP 40	• •
Rated Current AC max IEC UL: 15 A 15 A				
 <p>5003 Appliance Inlet DC Filter, ECO Design, Front- or Rear Side Mounting</p>	Snap-in/screw-on Front-/Rear-Side	Molex MLX -	-	
Rated Current AC max IEC UL: 16 A 20 A				
 <p>EC12 IEC Appliance Inlet C20 with Filter, Line Switch 2-pole</p>	Screw Front Side	C20 -	IP40	• •
 <p>5130 IEC Appliance Inlet C20 with Filter, ECO design, front or rear side Mounting</p>	Snap-in/screw-on Front-/Rear-Side	C20 -	IP40	• •
 <p>C20F IEC Appliance Inlet C20 with Filter, Front or Rear Side Mounting</p>	Snap-in/screw-on Front-/Rear-Side	C20 -	IP40	• •
 <p>C22F IEC Appliance Inlet C22 for hot Conditions, with Filter for high Temperatures, front side Mounting</p>	Snap-in/screw-on Front-/Rear-Side	C22 -	IP40	•
 <p>EF12 IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed)</p>	Screw Front Side	C20 -	IP 40	• •