






Product overview




Circuit Breakers for Equipment

Type	Number of poles	Rated voltage	Current range	Application				Protection			Options				Con-nection		Mounting					
				General purpose	Industrial applications	Power supply	Household and leisure	Thermal	Magnetic	Available without protection	Undervoltage protection	Illumination	Different printings	Auxiliary contact	Shunt contact	Remote tripping	Quick connect terminals	Screw terminals	PCB THT	Threaded neck	Snap-in front side	Snap-in rear side
 T9-611 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-16 A	•	•	•		•								•						
 T9-311 / 211 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-16 A	•	•	•		•								•						
 T9-711 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-16 A	•	•	•		•								•						
 T9-818 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-15 A	•	•	•		•								•						
 T9-817 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-12 A	•	•	•		•								•						
 T11 Reset type	1	240 VAC 48 VDC	0.05A-16 A	•	•	•		•					•			•	•	•			•	
 T12 Reset- or switch type	1	240 VAC 28 VDC	0.05-16 A	•	•	•		•					•	•		•	•					•
 T12-MSM Reset- or switch type	1	240 VAC 28 VDC	0.05-16 A	•	•	•		•					•	•		•	•					
 TM12 Reset- or switch type	1	240 VAC 28 VDC	0.05-16 A	•	•	•		•	•				•	•	•	•	•					•
 TM12-MSM Reset- or switch type	1	240 VAC 28 VDC	0.05-16 A	•	•	•		•	•				•	•	•	•	•					
 T13 Reset- or switch type	1	250 VAC 28 VDC	0.05-30 A	•	•	•		•								•	•					
 TA35 Switch type	1	240 VAC 32 VDC	0.05-20 A	•	•	•	•	•	•			•	•			•						•
 TA35 Switch type	2	240 VAC 60 VDC	0.05-20 A	•	•	•	•	•	•			•	•			•						•
 TA35 Switch type	3	240 VAC	0.05-12 A	•	•	•	•	•	•			•	•			•						•
 TA45 Switch type	2	240/400 VAC 60 VDC	0.05-20 A	•	•	•	•	•	•	•		•	•	•	•	•						•
 TA45 Switch type	3	240/400 VAC 60 VDC	0.05-12 A	•	•	•	•	•	•	•		•	•	•	•	•						•

Power Entry Modules with Circuit Breaker

Type	Current range	IEC 60320-1 inlet type	IEC plug type			Circuit breaker			Mounting			Con-nection	
			Protection class I	Protection class II	V-Lock cord retaining	CBE 1-pole protected	CBE 2-pole protected	Illuminated rocker	Components prewired	Screw-on front	Screw-on rear	Snap-in	Quick connect
	6145 double pole CBE, pre-wired	1-10A IEC 1-15A UL	C14/C18	•	•	•	•	•	•	•	•	•	•
	6135 double pole CBE	1-10A IEC 1-15A UL	C14	•	•	•	•	•	•	•	•	•	•
	6136 single pole CBE	12-16A IEC 12-20A UL	C20	•	•	•	•	•	•	•	•	•	•
	DF11 recessed switch, double pole CBE, pre-wired	1-10A IEC 1-15A UL	C14	•	•	•	•	•	•	•	•	•	•
	EF11 recessed switch, double pole CBE, pre-wired	12-16A IEC 12-20A UL	C20	•	•	•	•	•	•	•	•	•	•

Power Entry Modules with Circuit Breaker and Filter

Type	Current range	Inlet	IEC plug type			Circuit breaker			Mount- ing		Con- nection		Attenu- ation		Leakage current	
			Protection class I	Protection class II	V-Lock cord retaining	CBE 1-pole protected	CBE 2-pole protected	Illuminated rocker	Components prewired	Screw front	Snap-in	Quick connect	Wire leads on request	Standard 20 - 50 dB	High 40 - 70 dB	Medical <5µA
	DF12 recessed switch pre-wired, double pole CBE	1-10A IEC 1-15A UL	C14	•	•	•	•	•	•	•	•	•	•	•	•	•
	5145 pre-wired, double pole CBE	1-10A IEC 1-15A UL	C14/C18	•	•	•	•	•	•	•	•	•	•	•	•	•
	EF12 recessed switch pre-wired, double pole CBE	12-16A IEC 12-20A UL	C20	•	•	•	•	•	•	•	•	•	•	•	•	•

Web information

At schurter.com you can enter the connector type (e.g. TA35) into the search box and download the data sheets containing all relevant details.

Customized solutions

In addition to its broad product range, SCHURTER also offers individual services to fulfill all customer requirements.

We will build specific samples and provide you with your customized solution. schurter.com/cbe